



# AirFocus

*HIGH-PERFORMANCE OVERHEAD FAN*

Join the movement...



## Powerful Air Circulation

Designed to move impressive amounts of air, equalizing temperature and humidity, reducing the load on heating and cooling equipment, and improving the comfort and productivity of occupants at a fraction of the cost and complexity of HVLS fans.



## Whisper-Quiet Operation

More air, Less noise... Don't sacrifice communication for cooling. Sound levels are part of comfort and safety too. Kevlar belt-driven technology gives AMS fans amazing power and air movement, with ultra-low noise.



## Fast, Easy Installation

Simple, lightweight design and DIY-friendly Safe Strap installation method make getting your AMS fan up and running a breeze.

## SPECIFICATIONS

DIAMETER	59 inches (1.5 m)
WEIGHT	VS: 134 lbs. (60.8 kg); SS: 118 lbs. (53.5 kg)
ELECTRICAL	115-1P VAC (optional 230-1P VAC)
OUTPUT	43,000 CFM (1,360 m <sup>3</sup> /min)
MOTOR	1.5 HP, Inverter motor, Class F Insulation, TEFC Industry Duty, IP-55, UL
CONTROLS	<u>AirFocus VS</u> : Variable Speed VFD, IP-66 Enclosure; <u>AirFocus SS</u> : Single Speed
NOISE LEVEL	43.4 DB (20' from fan on axis)
WARRANTY	1-year Motor & Controls; 5-year Material & Workmanship


\* Black finish available for an additional charge \*

[www.AMSfans.com](http://www.AMSfans.com) - 1(888)319-1626

## COVERAGE AREA

### 6-AIRFOIL DESIGN (STANDARD)

Long, wide [ 75' (23 m) ] conical area of effect



### 3-AIRFOIL DESIGN (OPTIONAL)

Ultra-long, narrow [ 30' (9 m) ] conical area of effect

## SOUND LEVEL & DIMENSIONS

